



Code	Description	Dimensions				Image	
		D	S(+0.5)	LL(+0.2)	h1(MAX)		
B	Standard cut and formed leads	4.0	5	3.8	2.8		
		5.0	5	3.8	2.8		
		6.3	5	3.8	2.8		
		8.0	5	3.8	2.8		
F	cut and formed leads	D	S(+0.5)	LL(+0.2)	h1(MAX)		
		4.0	2.5	3.8	1.5		
CC	Standard Straight cut leads	D	S(+0.5)	LL(+0.2)			
		4.0	1.5	3.8			
		5.0	2.0	3.8			
		6.3	2.5	3.8			
		8	3.5	3.8			
		10-12.5	5.0	3.8			
SI	Formed snap-in leads	D	S(+0.5)	LL(+0.2)	f(+0.1)		
		4.0	5.0	4.2	1.1		
		5.0	5.0	4.2	1.1		
		6.3	5.0	4.2	1.1		
SI	Straight snap-in leads	D	S(+0.5)	LL(+0.2)	f(+0.1)		
		10-12.5	5.0	4.5	1.2		
		16-18	7.5	4.5	1.3		
E	90° bent leads	D	S(+0.5)	h(+0.5)	f(+0.2)		
		5.0	2.0	2.0	3.2		
		6.3	2.5	2.0	3.5		
		8	3.5	2.0	4.0		
		10	5.0	2.2	4.0		
		12.5	5.0	2.2	3.5		
C	90° bent leads	D	S(+0.5)	h(+0.5)	f(+0.2)		
		5.0	2.0	2.0	3.2		
		6.3	2.5	2.0	3.5		
		8	3.5	2.0	4.0		
		10	5.0	2.2	4.0		
		12.5	5.0	2.2	3.5		
HD	90° bent leads Offset leads	D	S(+0.5)	h(+0.5)	LL(+0.5)	f(+0.5)	
		12.5	5.0	4.0	10	3.8	
HF	90° bent leads Formed leads	D	S(+0.5)	h(+0.5)	h1(MAX)	f(+0.3)	
		8	5.0	2.0	1	3.7	